

POWERED BY **Dialog**

**Prepn. of conductive fibre deposited pyrrole polymer - by adhering pyrrole polymer to dimples on fibre surface, giving durability and stability**  
**Patent Assignee: TORAY IND INC**

**Patent Family**

Patent Number	Kind	Date	Application Number	Kind	Date	Week	Type
JP 1266280	A	19891024	JP 8892215	A	19880414	198948	B

**Priority Applications (Number Kind Date):** JP 8892215 A ( 19880414)

**Patent Details**

Patent	Kind	Language	Page	Main IPC	Filing Notes
JP 1266280	A		5		

**Abstract:**

JP 1266280 A

Prepn. of conductive fibre comprises adhering pyrrole polymer to the dimples on the surface of fibre.

The dimple is pref. more than 1 micron wide and more than 1 micron deep. The adhesion of the pyrrole polymer to dimple is carried out by adhering an oxidising agent to the dimples, pref. with an alcohol soln. and by making the dimples into contact with pyrrole. Before the adhesion of an oxidising agent to dimple, the fibre was impregnated in soln. contg. the oxidising agent.

**USE/ADVANTAGE** - The conductive fibre is used in clothings field, computers requiring barrier for electromagnetics, etc. The conductive fibre has good stability, friction resistance, washing resistance and durability.

Derwent World Patents Index

© 2004 Derwent Information Ltd. All rights reserved.

Dialog® File Number 351 Accession Number 8088783